

Large Display

D1002, D1004

- Available with 4 and 6 digits.
- Provided with and without Relay Output (alarms) and special output options.
- Remote setting from ground level.
- Very easy to programme and use. No-menu programming.



Specifications:

Functions:	Vetec Large Display is ideal in combination with load cells.
Input signals:	<ul style="list-style-type: none"> • Load cells. • 4-20mA, 0-10V, 1-5V etc. • Serial Data RS232, RS485, 422 etc.
Output options:	<ul style="list-style-type: none"> • 2 or 4 alarms SPST relays, 2x SPDT. • 4-20mA, 0-10V or -10 to +10 analog. • RS232, RS485, Ethernet data output.
IP Class:	IP65 for bottom glands, IP54 for top.
Materials:	Black polycarbonate.

Examples, all with load cell input.

Item No.:	Digits	Digit height	Viewing	Power Supply	Relay Output	Analogue Output
D1002/4-L-R-AC-3	4	57 mm	25 mtrs.	95-265 VAC	0	-
D1004/4-L-R-AC-3	4	102 mm	50 mtrs.	95-265 VAC	0	-
D1004/6-L-R-AC-3	6	102 mm	50 mtrs.	95-265 VAC	0	-
D1004/6-L-R-48VAC-3	6	102 mm	50 mtrs.	48 VAC	0	-
Item No.:	Digits	Digit height	Viewing	Power Supply	Relay Output	Analogue Output
D1002/4-L-AL2-R-AC-3	4	57 mm	25 mtrs.	95-265 VAC	2	-
D1004/4-L-AL2-R-AC-3	4	102 mm	50 mtrs.	95-265 VAC	2	-
D1004/6-L-AL2-R-AC-3	6	57 mm	25 mtrs.	95-265 VAC	2	-
D1004/6-L-AL2-R-48-3	6	102 mm	50 mtrs.	48 VAC	2	-
Item No.:	Digits	Digit height	Viewing	Power Supply	Relay Output	Analogue Output
D1004/4-L-ANI-AC-3	4	102 mm	50 mtrs.	95-265 VAC	0	4-20Ma
D1004/4-L-485-AC-3	4	102 mm	50 mtrs.	95-265 VAC	0	RS485
D1004/4-L-A2-RTU-AC-3	4	102 mm	50 mtrs.	95-265 VAC	2	MODBUS RTU
D1004/6-L-A2-RTU-AC-3	6	102 mm	50 mtrs.	95-265 VAC	2	MODBUS RTU

* Other displays can be provided to meet specific requirements and other applications.

Address
Lucernemarken 18 A
DK-5260 Odense S

Bank
Nykredit Bank

Bank Account
DKK 8117-4522421
EUR 117-9653680

IBAN no.
DKK DK7681170004522421
EUR DK1981170009653680

SWIFT code
NYKBKKK

VAT no.
27414621

24
www.vetec.dk

Telephone
+45 6590 5802

Mail
post@vetec.dk